

## Premier Tin-Lined Copper Tubing Supplier

Webco is the exclusive supplier of corrosion resistant TinGuard copper tubing. This unique tube is tin-lined at Webco utilizing one of a kind equipment and an innovative process for applying tin. Our coils offer beneficial thermal transfer properties and TinGuard offers corrosion resistance to damaging elements.

TinGuard is particularly valuable in natural gas applications, or any corrosive environment where bare copper requires extra protection. Our TinGuard copper tubing, made from seamless CDA-122 DHP copper, is dead soft tempered for easy workability and can be manufactured with tin-coated ODs, IDs or both.

Custom or standard 50-ft. lengths, individually packaged and boxed are available for quick shipping.

## Tin-Lined Copper Tubing Applications

Our customers depend on TinGuard copper tube products for a wide variety of uses, including but not limited to the following applications:

- > Outdoor Gas Lighting
- > Fire Suppression Systems
- > Connector Tube
- > Fuel Lines
- > Outdoor Gas Grills and Fireplaces
- > Oil Heat
- > Beverage Dispensing Equipment
- > Chemical Dispensing Equipment

| Part Number    | Size             | Outside Diameter | Wall Thickness | Weight   |
|----------------|------------------|------------------|----------------|----------|
| J0397725003050 | .250"OD X .030"W | 1/4"             | .030"          | 4 lbs    |
| J0397731203050 | .3125"OD X.032"W | 5/16"            | .032"          | 5.5 lbs  |
| J0397737503050 | .375"OD X.032"W  | 3/8"             | .032"          | 6.7 lbs  |
| J0397750003050 | .500"OD X .032"W | 1/2"             | .032"          | 9.1 lbs  |
| J0397762503050 | .625"OD X.035"W  | 5/8"             | .035"          | 12.6 lbs |

## Contact Information for TinGuard Coils

|  |                       |  |
|--|-----------------------|--|
| <a href="http://webcoindustries.com">webcoindustries.com</a>   1099A Hill Ave   Glen Ellyn, IL 60137 USA |                       |  |
| Sales Support  | 630-469-8150 (Office) | <a href="mailto:brandone@webcoindustries.com">brandone@webcoindustries.com</a> |